

Econoflo Upflow Neutralizer

Econoflo UNF Neutralizing Filter

Econoflo UNF contains special media which raises the pH of acidic water and neutralizes its acidic characteristics. In addition to protecting pipes, plumbing fixtures and appliances, this filter also facilitates the removal of iron and manganese by raising the pH to enable an iron filter to be used. After a period of time, additional media may be required.

Features

- Heavy duty fiberglass resin tanks with a **10 YEAR** guarantee
- Removable closure with internal screen allows refilling media without disconnecting plumbing
- Designed for simple operation and service

Specifications and Performance

Model Description	Media cu.ft. (l)	Flow Rates		Installation Space W x D x H inches (mm)	Mineral Tank Size inches (mm)	Shipping Weight lbs (kg)
		Service usgpm (l)	Peak usgpm (l)			
UNF10	1 (28)	3 (11.4)	5 (19)	11 x 11 x 50 (279 x 279 x 1270)	10 x 47 (254 x 1194)	100 (45.4)
UNF20	2 (56)	6 (23)	10 (38)	13 x 13 x 55 (330 x 330 x 1397)	12 x 52 (305 x 1321)	200 (91)

Maximum Water Temperature = 110°F (43°C)

Maximum Operating Pressure = 100 PSIG (689 kPa)

Pipe Size = Standard Connection - 1" MNPT; Optional Connection - 1" BSPM

Peak flow rates intended for intermittent use only (10 minutes or less) and are for residential applications only. Do not use peak flow rates for commercial applications.

- At the stated service flow rates, the pressure drop through these devices will not exceed 15 psig.
- The manufacturer reserves the right to make product improvements which may deviate from the specifications and descriptions stated herein, without obligation to change previously manufactured products or to note the change.
- Approved for use in the state of Wisconsin



WATERGROUP INC.

FRIDLEY, MN
1-800-354-7867

www.watergroup.com

WATERGROUP COMPANIES INC.

REGINA, SK • CAMBRIDGE, ON
1-877-288-9888

#57138 Rev. 4/08
Printed in Canada

