



150 Monument Road
Bala Cynwyd, PA 19004
800-343-1500 610-668-9090

Material Safety Data Sheet

complies with:
OSHA's Hazard Communication Standard,
29 CFR 1910.1200

IDENTITY (As Used on Label and List)

A-400, A-400 SC, NRW-400, A-444, A-500, A-500 SC, NRW-500, A-500P, A-501P, A-600, A-600 SC, NRW-600, SGA-550 in the chloride form for the following particle size grades: Standard (STD), MB, PL, CL, FL, TL, DL Strong, S, C, G and PUROFINE

CAS #

69011-19-4

SECTION I Manufacturer's Name & Contact Information

Purolite Hazard Rating

Scale

The Purolite Company 150 Monument Road Bala Cynwyd, PA 19004 , USA	Emergency Telephone Number: 610-668-9090	Toxicity	1	4 = Extreme 3 = High 2 = Moderate 1 = Slight 0 = Insignificant
	Telephone # for Information: 610-668-9090	Fire	1	
	Date Prepared: 19. April 2007	Reactivity	0	
		Special	-	

SECTION II Ingredients/Identity Information

Components (Specific Chemical Identity: Common Name(s))	OSHA	PEL	ACGIH TLV	Other Limits
Quaternary amine styrene divinylbenzene copolymer in the chloride form -- 35 - 65% Water -- 35 - 65%	N/A	N/A	N/A	N/A

SECTION III Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H ₂ O = 1)	Approx 1.2	Solubility in Water	Negligible
Vapor Pressure (mm Hg)	N/A	Evaporation Rate (Butyl Acetate =	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Appearance and Odor	Spherical beads with slight amine (fishy) odor when new		

SECTION IV Fire and Explosion Hazard Data

Flash Point (Method Used)	None	Flammable Limits auto/ign. 427°C / 800° F (estimated) No flash point	LEL	UEL
			N/A	N/A
Extinguishing Media	CO ₂ Dry chemical, Water fog			
Special Fire Fighting Procedures	Wear MSHA /NIOSH approved, pressure demand, self contained breathing apparatus			
Unusual Fire and Explosion Hazards	None			

SECTION V - Reactivity Data

Stability	Stable	Conditions to Avoid	Avoid temperatures over 220°C (424°F)
Incompatibility (Materials to Avoid)	Avoid contact with concentrated nitric acid, or strong oxidizing agents.		
Hazardous Decomposition or Byproducts	CO, CO ₂ , Styrene monomer, N (CH ₂ OH), NH ₃ , Divinylbenzene		

Hazardous Polymerization	Will not occur	Conditions to Avoid	N/A
--------------------------	----------------	---------------------	-----

A-400, A-400 SC, NRW-400, A-444, A-500, A-500 SC, NRW-500, A-500P, A-501P, A-600, A-600 SC, NRW-600, SGA-550 in the chloride form for the following particle size grades: Standard (STD), MB, PL, CL, FL, TL, DL Strong, S, C, G and PUROFINE

SECTION - VI Health Hazard Data							
Route(s) of Entry: N/A		Inhalation?	N/A	Skin?	N/A	Ingestion?	N/A
Health Hazards (Acute and Chronic)		Eye Contact: Like other foreign bodies, particles may cause mechanical irritation of the eye					
Carcinogenicity	N/A	NTP?	N/A	IARC Monographs?	N/A	OSHA Regulated?	N/A
Signs and Symptoms of Exposure		N/A					
Medical Conditions Generally Aggravated By Exposure		Eye Contact: Like other foreign bodies, particles may cause mechanical irritation of the eye					
Emergency and First Aid Procedures		Eye contact: May cause slight alkaline irritation. Flush with large amount of water for at least 15 minutes. Consult physician if irritation persists					
SECTION VII - Precautions for Safe Handling and Use							
Steps to be Taken in Case Material is Released or Spilled: Resin beads on floor may mechanically cause floor to be slippery. Use care to avoid falls. Sweep up and transfer to containers for recovery or disposal							
Waste Disposal Method				Dispose of in accordance with Federal, State and Local Regulations			
Precautions to be Taken in Handling and Storing:				Keep drums and plastic bags sealed to prevent drying or moisture loss.			
Other Precautions:				Store below 49° (120°F) and above 0°C (32°F)			
SECTION VIII - Control Measures							
Respiratory Protection (Specify Type)				None			
Ventilation		Local Exhaust	Normal room ventilation		Special	N/A	
		Mechanical (General)	N/A		Other	N/A	
Protective Glove:		Cloth gloves		Eye Protection:	Safety glasses (ANSI Z 87.1)		
Other Protective Clothing or Equipment				None			
Work/Hygienic Practices				Cleanliness is recommended.			