

WaterGroup®


Hydrogen Sulfide Reduction AIO Filter

Does Your Water Stink?

Hydrogen sulfide (H₂S) is a nuisance. It adds an objectionable sulfur-like taste and "rotten egg" odor to drinking water. Left untreated, it can also lead to corrosion in plumbing pipes and fixtures.

Features:

- ➔ Combines aeration with catalytic carbon technology to effectively reduce sulfur from water.
- ➔ No more bad taste or odor.
- ➔ No Chemicals to buy, mix or add
- ➔ No weekly water tests to perform
- ➔ Simple, Fully Automatic regeneration with Air



AIO (Air Induction Oxidizer) Filter For Hydrogen Sulfide Reduction (Single Tank)

Specifications	WG665AIOC-075	WG665AIOC-100	WG665AIOC-150
	2238	2239	2240
Cat Carbon Cu Ft	0.75	1.0	1.5
Flow Rate USGPM			
- Service	2	3	4
- Peak	4	6	10
- Backwash	3.5	4	5
Mineral Tank Size	8 x 44	9 x 48	10 x 54
Pipe Size Inches	3/4"	3/4"	3/4"
Ship Weight Lbs	110	145	250



Bed Type	Application Parameters			
	Iron (ppm)	Manganese (ppm)	Hydrogen Sulfide (ppm)	pH Range
AIOC Catalytic Carbon	0.0	0.0	0.0 - 3.0	7.0 - 8.5

Your Local Plumbing Professional

Toll Free: 1-877-288-9888
www.watergroup.com

Regina, SK • Cambridge, ON • Whitestown, IN
Phoenix, AZ • Houston, TX • Guadalajara, MX