

WaterGroup®

665 BIF Series Filter System

Remove Stubborn Iron, Manganese and Sulphur Without Chemicals


Features:

- Natural oxidation removes iron, manganese and hydrogen sulfide without chemicals, air pumps or a venturi
- Low maintenance two tank system
- Regenerates less frequently than traditional iron filters using up to 50% less water than single tank iron filters
- NSF Certified electronic control valve
- NSF Certified fibreglass pressure tanks
- Meter Immediate, Meter Delayed, Meter with Day Override, and Calendar Clock mode
- Adjustable cycle times
- Unique bypass with an integrated space saving turbine meter and sample port on the inlet. One-piece design avoids meter jamming
- Time saving quick connect fittings on bypass
- Quick connect drain line O-ring eliminates need for Teflon
- Power cord even has quick connect for easy valve spin on
- Hose clamp and 10' of drain tubing included



Uses up to
50% Less Water!



 IAPMO R & T Certified
Against NSF/ANSI 42

Item #	Model	Media Cu Ft	Flow Rate USGPM			Mineral Tank Size	Air Contact Tank	Pipe Size Inches	Ship Weight Lbs
			Service	Peak	Backwash				
2480-1	WG665BIF-100	1.0	3.0	6.0	5.0	10 x 44	10 x 44	3/4"	170
2481-1	WG665BIF-150	1.5	4.0	10.0	5.0	10 x 54	10 x 54	3/4"	200
2486-1	WG665BIFMN-100	1.0	3.0	6.0	5.0	10 x 44	10 x 44	3/4"	168
2487-1	WG665BIFMN-150	1.5	4.0	10.0	5.0	10 x 54	10 x 54	3/4"	197
2484-1*	WG665BIFMM-100 with Multi Media	1.0	3.0	6.0	5.0	10 x 44	10 x 44	3/4"	149
2485-1*	WG665BIFMM-150 with Multi-Media	1.5	4.0	10.0	7.0	10 x 54	10 x 54	3/4"	164
2482-1	WG665BIFCC-100 with Catalytic Carbon	1.0	3.0	6.0	5.0	10 x 44	10 x 44	3/4"	100
2483-1	WG665BIFCC-150 with Catalytic Carbon	1.5	4.0	10.0	5.0	10 x 54	10 x 54	3/4"	117

- BIF MN Models for low pH and/or high manganese applications
 - BIF Iron and Hydrogen Sulfide Filter With Multi Media For Use on Tannin Bearing Water
 - BIF Hydrogen Sulfide Removal With Catalytic Carbon For Higher Than Normal H2S Removal (up to 5.0 ppm)
- Contact Customer Service or Your Sales Representative for Application Guidelines

***Media not loaded in mineral tank.**

Maximum Iron	BIF and BIFMN models 30.0 ppm / BIF Multi Media models 10.0 ppm / BIF Catalytic Carbon models 0.0 ppm
Hydrogen Sulfide	BIF and BIF Multi Media 1.0 / BIFMN 3.0 ppm / BIF Catalytic Carbon 5.0 ppm
Manganese	BIF, BIF Multi Media and BIF Catalytic Carbon 0.0 ppm / BIFMN models 1.0 ppm
Iron Bacteria Removal	No
pH	BIF Multi Media pH 7.2 - 8.5 / BIF and BIF Catalytic Carbon pH 7.0 - 8.5 / BIFMN models pH 6.5 - 7.5



WG 665 Valve



5 Year Warranty Control Valve



10 Year Warranty Pressure tank



A Division of



WaterGroup®

Toll Free: 1-877-288-9888

www.watergroup.com

Regina, SK • Cambridge, ON • Whitestown, IN

Phoenix, AZ • Houston, TX • Guadalajara, MX

Your Local Plumbing Professional

80155655 2024-04-19
Download only.