

WaterGroup®

WG NRV (Non-Regenerating Valve) Whole House Carbon Filter

Economical Reduction of Chlorine and Other Bad Taste & Odors

Once water arrives safely at your home there is no further need for disinfectants. In fact they are undesirable! Disinfectants cause taste and bad odor, dry skin, damage plumbing, and can produce potentially harmful by-products.



**97% Chlorine
Removal!
Over 1,100,000
gallons**



Certified by IAPMO R&T
to NSF/ANSI 42 for
Chlorine Reduction



NRVTO-150



Economical Reduction of Chlorine, Chloramines and other bad taste & Odors.

Features:

- ➔ Economical whole-house carbon filtration solution for reducing chlorine and other bad tastes and odors. TOCK models reduce chlorine, chloramines plus hydrogen sulfide (H₂S) caused by sulphate reducing bacteria common in warmer climates.
- ➔ Factory installed one-piece bypass
- ➔ Time saving quick connect fittings (90° 3/4" NPT elbows NPT) included for faster, easier installation. Optional quick connect SharkBite® fittings also available.
- ➔ Five year warranty on distribution head
- ➔ Ten Year warranty on NSF certified tank

90° 3/4" NPT Elbows



Economical non-back-washing distribution head with convenient quick connect fittings

| Specifications | NRV TO-100 15054073 | NRV TO-150 15054074 | NRV TOK-100 15054075 | NRV TOK-150 15054076 |
|----------------------------------|--------------------------------------|------------------------|--|--|
| Peak Flow Rates | 4.0 gpm | 5.0 gpm | 4.0 gpm | 5.0 gpm |
| Filter Media Volume - Cubic Feet | 1.0 ft ³ | 1.5 ft ³ | 1.0 ft ³ | 1.5 ft ³ |
| Filter Tank Size (inches) | 9 x 48 | 10 x 54 | 9 x 48 | 10 x 54 |
| Media Type | Coconut Carbon | Coconut Carbon | Coconut Carbon With KDF Distributor | Coconut Carbon With KDF Distributor |
| Media Loaded | Yes | Yes | Yes | Yes |
| KDF Protector | No | No | Yes | Yes |
| Tank Jacket | No | No | No | No |
| Shipping Weight | 60 lbs | 78 lbs | 60 lbs | 78 lbs |
| Plumbing Connections | Includes 3/4" 90° Elbows NPT | | | |
| Electrical Requirements | None | | | |
| Water Temperature | Min 39 - Max. 100 degrees Fahrenheit | | | |
| Water Pressure | Max. 125 psi | | | |

The life expectancy of the carbon media bed in these units will be reduced as compared to a back washing style carbon filter. The actual media bed life will vary depending on water consumption, chlorine/chloramines concentration and flow rate. Exceeding the peak flow rate listed above will drastically reduce the life expectancy of the carbon media.



Certified by IAPMO R&T
to NSF/ANSI 42 for
Chlorine Reduction



Toll Free: 1-877-288-9888
www.watergroup.com

Regina, SK • Cambridge, ON • Whitestown, IN
Phoenix, AZ • Houston, TX • Guadalajara, MX

Your Local Plumbing Professional

80156017 2023-10-10
Download only