


WaterGroup®

465 BIF Series Filter System

Remove Stubborn Iron, Manganese and Sulphur Without Chemicals

Features:

- Natural oxidation removes iron, manganese and hydrogen sulfide without chemicals, air pumps or a venturi
- Low maintenance two tank system
- Regenerates less frequently than traditional iron filters using up to 50% less water than single tank iron filters
- NSF Certified electronic control valve
- NSF Certified fibreglass pressure tanks
- Meter Immediate, Meter Delayed, Meter with Day Override, Vacation and Calendar Clock mode
- Adjustable cycle times
- Unique bypass with an integrated space saving turbine meter and sample port on the inlet. One-piece design avoids meter jamming
- Time saving quick connect fittings on bypass
- Quick connect drain line o-ring eliminates need for Teflon
- Power cord even has quick connect for easy valve spin on
- Hose clamp and 10' of drain tubing included



Item #	Model	Media Cu Ft	Flow Rate USGPM			Mineral Tank Size	Air Contact Tank	Pipe Size Inches	Ship Weight Lbs
			Service	Peak	Backwash				
2199-1	WG465BIF-100	1.0	3.0	6.0	5.0	10 x 44	10 x 44	3/4"	150
2200-1	WG465BIF-150	1.5	4.0	10.0	5.0	10 x 54	10 x 54	3/4"	188
2206-1	WG465BIFMN-100	1.0	3.0	6.0	5.0	10 x 44	10 x 44	3/4"	150
2207-1	WG465BIFMN-150	1.5	4.0	10.0	5.0	10 x 54	10 x 54	3/4"	188
940662-1*	WG465BIFMM with Multi Media	1.0	3.0	6.0	5.0	10 x 44	10 x 44	3/4"	150
940663-1*	WG465BIFMM-150 with Multi-Media	1.5	4.0	10.0	7.0	10 x 54	10 x 54	3/4"	188
940366-1	WG465BIFCC-100 with Catalytic Carbon	1.0	3.0	6.0	5.0	10 x 44	10 x 44	3/4"	150
940365-1	WG465BIFCC-150 with Catalytic Carbon	1.5	4.0	10.0	5.0	10 x 54	10 x 54	3/4"	188

- BIF MN Models for low pH and/or high manganese applications
 - BIF Iron and Hydrogen Sulfide Filter With Multi Media For Use on Tannin Bearing Water
 - BIF Iron & Hydrogen Sulfide Removal With Catalytic Carbon For Higher Than Normal H2S Removal (up to 5.0 ppm)
- Contact Customer Service or Your Sales Representative for Application Guidelines

***Media not loaded in mineral tank.**

Maximum Iron	BIF and BIFMN models 30.0 ppm / BIF Multi Media models 10.0 ppm / BIF Catalytic Carbon models 0.0 ppm
Hydrogen Sulfide	BIF 1.0, BIFMN and BIF Multi Media 3.0 ppm / BIF Catalytic Carbon 5.0 ppm
Manganese	BIF, BIF Multi Media and BIF Catalytic Carbon 0.0 ppm / BIFMN models 1.0 ppm
Iron Bacteria Removal	No
pH	BIF, BIF Multi Media and BIF catalytic Carbon pH 7.0 - 8.5 / BIFMN models pH 6.5 - 7.5



7 Year Warranty
Control Valve



Lifetime Warranty
Pressure tank

A Division of



WaterGroup®

Toll Free: 1-877-288-9888

www.watergroup.com

Regina, SK • Cambridge, ON • Whitestown, IN

Phoenix, AZ • Houston, TX • Guadalajara, MX

Your Local Plumbing Professional

80156016 2023-11-17
Download only.